

Kategori **Kabler**

Viablue X Silver Powerkabel

Model/Varenr.: 99328

Pris fra 172,50 DKK

ViaBlue™ X-Silver power cables supply high-end audio and video equipment with clean power. The double screening keeps out interfering frequencies. The X-25 sets out the basis for a completely clean and crystal clear sound. External disturbances have no influence on the signals being transmitted. The double screening of 100% aluminum-laminated foil and 93% tinned copper braid with 32 strands guards against interference from electromagnetic (EM) and radio frequency (RF) sources. The external diameter of the X power cable is 13 mm. The X Silver is very flexible and elastic. The X Silver has certifications of VDE, HAR, UL, CUL / CE. Non-shielded power cords may act as antennas. Thus, external interference fields have effects on the frequencies of the signals. The ViaBlue™ X Silver cord with 100% covering shields blocks these external interference fields. For a properly functioning system, it is necessary to transport electrical power clean and trouble-free to all connected devices and giving the complete system that depends on the incoming power an optimum of interference-free basis. The X Silver sets out the basis for a completely clean and crystal clear sound. External disturbances have no influence on the signals being transmitted. Full transfer of the entire spectrum is given by technical linearity.

Technical specifications:

- Outer diameter: X-25 13 mm | X-40 14 mm | X-60 16mm
- Diameter of single conductors: 3x 2,5 mm² | 3x 4,0 mm² | 3x 6,0 mm²
- Shieldings: Alu-PE Foil | 32x 0.10 braid
- Rohs conform



- Finishing: silvered / tinned
- Isolation resistance: > 20 MOhm x KM
- Isolation: PVC TM2, VDE 0472
- Test voltage: 3000 Volt
- Burn in time: ca. 16 hours
- Approvals: VDE | CE | UL | CSA
- Conductor's colours: black | blue | yellow-green

2.5 mm2 (Model/Varenr.: 98716)	172,50 DKK
4.0 mm2 (Model/Varenr.: 98717)	255,00 DKK
6.0 mm2 (Model/Varenr.: 98718)	345,00 DKK